



motorsport range **CAR1249ZG06**

6-piston radial mount caliper

Part numbers and handing

Disc thickness	Position	Ø30.2/34.9/38.1 pistons
30-32mm	LH trailing	CAR1249ZG06PESLT
	RH trailing	CAR1249ZG06PESRT
	LH leading	N/A
	RH leading	

Replacement parts

Item	Ø30.2/34.9/38.1 pistons
Seal Kit, axle set,	CSK303538E751
Pistons, STAINLESS STEEL, each	PSV3027X250E PSV3527X250E PSV3827X250E
AKB Springs, each	SSC3435X609 (x4) SSC3435X623 (x2)
Wear Plates, each	PSC4423X300L (x2) PSC4423X300R (x2)
Bleed Screw, each	FSB3430X371
O Seal	SER0080X445
Copper gasket	FCG0080X015

Applications:
Trophy Truck, Rally Raid



Key features and benefits

- Cross drilled stainless steel pistons with wear resistant coating.
- Internally ported, no external fluid transfer pipe.
- Bleed screws recessed for protection and fitted with sealed caps to keep them clean.
- Fluid inlet positioned in the underside of the housing for protection.
- Central bridge with facility for cooling duct to direct air across the caliper to cool the outer half.

Specifications

- Disc diameter range: Ø355 to 370mm.
- Disc thickness range: 30 to 32mm.
- Fluid inlet M10x1 female.
- Dry weight 2.53kg excluding pads.
- Alcon pad reference: 4494, 18mm thick, 164mm long, 50.5mm deep, area 164cm² per caliper.

Installation dimensions

